



REGARDING PREDRILLED AND CUSTOMER DRILLED HOLES IN STENI PANELS

As of April 2020 the predrilled holes in all Steni Colour and Steni Vision panels will be Ø6,5 mm. This is done to allow for more lateral movement of the panels caused by thermal expansion.

As a consequence we will also start supplying Ø6,0 mm drillbits to our customers who needs to drill the panels on-site.

As a rule of thumb we recommend that the diameter of the predrilled hole be at least 1,5 times the diameter of the fastener.

ANGÅENDE FORBOREDE HULL OG BORING AV STENI PLATER PÅ BYGGEPLASS

Fra og med April 2020 leveres alle Steni Colour og Steni Vision plater med Ø6,5 mm forborede hull. Dette gjøres for å tillate større sideveis bevegelse grunnet termisk ekspansjon.

Som en konsekvens av dette vil vi også levere Ø6,0 mm bor til de kunder som skal bore platene på byggeplass.

Som en tommelfinger regel anbefaler vi at diameteren på hullene i platen er minst 1,5 ganger diameteren på festemiddelet.

Berganmoen 16 April 2020

Product Management Dept.

A handwritten signature in black ink, appearing to read "Jan Marius Kruse". The signature is written in a cursive, flowing style.

Jan Marius Kruse